

# ZCKD21

Limit switch head, Limit switches XC Standard, ZCKD, thermoplastic roller lever plunger horizontal direction

## Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product Compatibility	XCKM XCKL
Associated body	ZCKMD35 ZCKMD31H7 ZCKL5H7 ZCKLD35 ZCKMD39H29 ZCKLD31H7 ZCKLD35H7 ZCKM6H7 ZCKL6 ZCKM8H29 ZCKM7H29 ZCKLD39H7 ZCKMD37 ZCKMD35H7 ZCKLD37 ZCKM1 ZCKL1H7 ZCKLD39 ZCKMD39H7 ZCKMD31H29 ZCKM5H7 ZCKL6H7 ZCKMD31 ZCKM7H7 ZCKM9 ZCKMD37H29 ZCKM6 ZCKM1H29 ZCKL1 ZCKLD37H7 ZCKM6H29 ZCKM8 ZCKM1H7 ZCKM7 ZCKL5 ZCKM5 ZCKM9H29 ZCKM5H29 ZCKL8 ZCKL8H7 ZCKLD31 ZCKL7H7 ZCKMD37H7 ZCKMD35H29 ZCKMD39 ZCKL7 ZCKM8H7
Movement of operating head	Rotary Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach, 1 direction

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

## Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment


## Ordering and shipping details

Category	US1000T22416
Discount Schedule	000T
GTIN	3389110646726
Returnability	Yes
Country of origin	ID

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.38 in (3.500 cm)
Package 1 Width	2.48 in (6.300 cm)
Package 1 Length	2.95 in (7.500 cm)
Package 1 Weight	2.998 oz (85.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	28
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.864 lb(US) (2.660 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	896
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	203.152 lb(US) (92.148 kg)

## Offer Sustainability

SCIP Number	062cf9d1-b407-4c29-893d-fbdcffcc97ce
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------