



Main

Range of Product	Powerpact
Product or Component Type	Earth leakage add-on block
Circuit breaker type	HJ HG HL HD

Complementary

Line Rated Current	15...150 A
Network type	AC
[Ue] rated operational voltage	240...600 V
Earth-leakage sensitivity	1000 MA 30 MA 3000 MA 300 MA 100 mA
Earth-leakage protection time delay	500 ms Instantaneous
Local signalling	Trip indicator
Electrical connection to mcb	Plug in
Tightening torque	79.66 Lbf.In (9 N.m) 0.00...0.08 in ² (2.5...50 mm ²) (AWG 14...AWG 1/0) 79.66 Lbf.In (9 N.m) 0.00...0.08 in ² (2.5...50 mm ²) (AWG 12...AWG 1/0) 39.83 Lbf.In (4.5 N.m) 0.00...0.08 in ² (2.5...50 mm ²) (AWG 12...AWG 10) 150.46 lbf.in (17 N.m) 0.08...0.19 in ² (50...120 mm ²) (AWG 4...AWG 1)

Environment

Product certifications	CSA UL
------------------------	-----------

Ordering and shipping details

Category	00916-GROUND FAULT EQUIPMENT
Discount Schedule	DE2
GTIN	785901565208
Nbr. of units in pkg.	1
Package weight(Lbs)	3.74 lb(US) (1.696 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.40 in (16.256 cm)
Package 1 width	5.30 in (13.462 cm)
Package 1 Length	10.60 in (26.924 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------