

# Rittal – The System.

Faster – better – everywhere.



## TS 8612.260

## TS punched rail, 18 x 38 mm

State: 9/22/2025 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 8612.260 - TS punched rail, 18 x 38 mm

Mounted on vertical TS enclosure profiles at the outer mounting level, on TS enclosure profiles and on base configuration rails for CM.



## Features

Model No.	TS 8612.260
Product description	Simply locate and secure with a screw. Location system makes installation and removal easy. Only needs to be secured on one side, but can be secured on both sides if necessary.
Material	Carbon steel
Supply includes	Assembly screws
Installation options	On the vertical TS, VX SE enclosure section on the outer mounting level On the horizontal TS, VX SE enclosure section On base configuration rail for TP
Note	In enclosures with a mounting plate, two punched rails are already included in the scope of supply.
Suitable for	Suitable for width/depth: 600 mm Suitable for width/depth: 23.6 "
Packaging unit	4 pc(s).
Net weight	2.5
Gross weight	2.669
Customs tariff number	73269098
EAN	4028177213104

# Features

---

ETIM 9	EC002625
ECLASS 8.0	27189234

---