



SKU: CLNS-350-38

UPC: 0783669642940

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 350, 1 Hole, 3/8in Bolt Size, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-71
ILSCOs Die Index Number	I-71
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2
Barrel Length (mm)	50.8
Dimension G (IN)	0.423
Dimension G (mm)	10.7442
Height (IN)	0.93
Height BX (IN)	2.25
Height (mm)	23.622
Inside Diameter (IN)	0.703
Inside Diameter (mm)	17.8562
Length (IN)	3.498
Length (mm)	88.8492
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.89
Outside Diameter (mm)	22.606
Strip Length (mm)	52.3748
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498

Tang Width (IN)	1.291
Tang Width (mm)	32.7914
Weight (LB)	0.252917628128448
Weight BX (LB)	3.457
Width (IN)	1.291
Width BX (IN)	5
Width (mm)	32.7914

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	350 kcmil - 3/0 Str
Flex Conductor Range	250 I,K,M 262.2 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366964294

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature



Temperature Rating

90°C

Color

Color

Silver

Color Code

Red

Voltage

Voltage Rating

35 kV