



# BIT4FX, Single Sided Flex Rated Two Conductor Clear Insulated Multi-Tap Connector

By Burndy  
Catalog # [BIT4FX](#)



Aluminum UNITAP, Tap - Same Side Entry, #14-#4 Class B & C,  
#14-#6 Class G,H,I,K, DLO, 2 PORT

## Application

Clear Insulated Multiple Tap Connectors

## General

Color Code	Brown
Connector Type	Multi Tap
EU RoHS Indicator	Yes
Hex Key	1/8 in
Insulation	Y
Insulation Type	Plastisol
Material	Aluminum
Number Of Ports	2
Plated	Y
Plating Type	Tin Plated
Sub Brand	UNITAP
Temperature Rating	135°C
Trade Name	UNITAP™
Type	BIT, UNITAP
UPC	621945440036
UPC 12 Digit	6219454400366

## Dimensions

Dimension - Height inch	1.25 in
Dimension - L Length Overall mm	27.44 mm
Dimension - Length Overall inch	1.08 in
Dimension - Width inch	1.13 in
Dimension - Width mm	28.70 mm

## Electrical Ratings

Operating Voltage	600 V
Voltage - Maximum	600 V

## Conductor Related

Conductor - AL Str Size Range	14 str.- 4 str.
Conductor - Copper DLO Size Range	14 str.-6 str.
Conductor - Copper Flex G Size Range	14 str.-6 str.
Conductor - Copper Flex H Size Range	14 str.-6 str.
Conductor - Copper Flex I Size Range	14 str.-6 str.
Conductor - Copper Flex K Size Range	14 str.-6 str.
Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Size	14-4 AWG
Conductor Type	<ul style="list-style-type: none"><li>AL C Str-Size</li><li>CU C Str-Size</li><li>CU C Flex-Size</li></ul>

## Certifications and Compliance

Certification - CSA Approved	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

[Catalogs - UNITAP™ Products](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - 50046931](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-BIT4FX-SPEC-EN | REV 1/2024

