

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



### Features and Benefits

- Replacement for conventional fluorescent T8 and T12 linear tubes
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Approximately 50% more energy efficient when compared to Fluorescent T8 lamps
- Works with non-shunted sockets ONLY
- Separate wiring harness and socket kit accessory available
- 50,000 hour Lifespan
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Instant on full brightness
- Environmentally friendly, no mercury used
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)

### Technical Specifications

<b>Performance</b>	<b>Dimmable:</b>	<b>Beam Angle:</b>
<b>Product Type:</b> Linear	No	240°
<b>Input Wattage:</b> 15W	<b>Construction</b>	<b>For Use Outdoors in Open Fixtures:</b>
<b>Lumens (Nominal):</b> 1800lm	<b>Material:</b> Glass	No
<b>Efficacy:</b> 120 lm/W	<b>Bulb Shape:</b> T8	<b>Other</b>
<b>Color Accuracy (CRI):</b> 82 CRI	<b>Nominal Length:</b> 4FT	<b>Equivalency:</b> 32W Fluorescent
<b>L70 Lifespan:</b> 50,000 Hours	<b>Finish:</b> Frosted	<b>Warranty (Years):</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a> .
	<b>Base Type:</b> G13	<b>LED Characteristics</b>
		<b>Color Temperature:</b> 5000K Daylight

## Technical Specifications (continued)

### Electrical

#### Operating Temperature:

-20°C - 45°C

#### Input Voltage:

100-277V

#### Operating Frequency:

50/60 Hz

### Installation

#### Installation Type:

Type B, Single Ended wiring

### Compliance

#### UL Recognized:

Yes

#### UL Classified:

Yes

#### NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

#### CEC Status:

Lawful for sale in California

### Application:

Suitable for damp locations and totally enclosed fixtures.

#### DLC Model Number:

T8-15-48G-850-SE-BYP

#### DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5 requirements.

DLC Product Code: PDE67QUX


## Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
48.8 x 22.4 x 2.0	4

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	49.2	7.9	7.3
PALLET	30	49.2	39.4	48.8

## Wiring Diagram



## Dimension

