



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series high speed cylindrical fuse

FWX-5A14F

UPC:051712795548

Dimensions:

- **Height:** 14 MM
- **Length:** 51 MM
- **Width:** 14 MM

Weight:22.4 G

Warranties:

- Not Applicable

Specifications:

- **Type:** Fuse
- **Application:** protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
- **Voltage Rating:** 600V
- **Voltage Rating Numeric:** 250 V
- **Amperage Rating:** 5A
- **Amperage Rating Numeric:** 5 A
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 250 Vdc
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 14 x 51 mm
- **Packaging Type:** Standard
- **Breaking Capacity:** 200 A
- **Clearing (I²T):** Clearing at 250V: 13
- **Frequency Rating Maximum:** 62 HZ
- **Frequency Rating Minimum:** 45 HZ
- **Fuse Shape:** cylindrical
- **Fuse Indicator:** Non Indicating
- **Pre Arc (I²T):** 1.6
- **Release Characteristic:** Other
- **Utilization category:** aR (accompanied semiconductor protection)



- **Voltage Type:** AC/DC
- **Watt Losses:** 1.3W
- **With Striker:** No

Supporting documents:

- [Product Catalog](#)

Certifications:

- UL Recognized

Product compliance:

- CE Marked