



Main

| | |
|----------------------------|--|
| Product | Sealed Transformer |
| Certifications | UL Listed |
| Type | Mini Power-Zone |
| Enclosure Code | CC |
| Insulation Temperature | 365 °F (185 °C) |
| Phase | 3 phase |
| Primary Voltage | 480 V |
| Secondary Voltage | 208Y/120 V |
| Full Capacity Taps | 2 5 % FCBN |
| Power Rating | 30 kVA |
| Temperature Rise | 115 °C |
| Winding Material | Copper |
| Interrupt Rating | 25 kA |
| Circuit Breaker Type | Primary main breaker Secondary main breaker Feeder breaker |
| Interior Type | NQ Panelboard interior |
| Number of Spaces Available | 24 |
| Number of Circuits | 24 |
| Enclosure Type | NEMA 3R hot-rolled steel |

Ordering and shipping details

| | |
|-----------------------|-----------------------------|
| Category | 16276-MPZ BOLT-ON BRANCH CB |
| Discount Schedule | PE2 |
| GTIN | 785901677437 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 830.00 lb(US) (376.482 kg) |
| Returnability | No |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 14.49 in (36.8 cm) |
| Package 1 width | 29.13 in (74 cm) |
| Package 1 Length | 51.26 in (130.2 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

| | |
|-----------------------|--|
| China RoHS Regulation | China RoHS Declaration |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
