

Product data sheet

Characteristics

QOB120VHCAFI

Mini circuit breaker, QO, 20A, 1 pole,
120/240VAC, 22kA, combo arc fault, pigtail,
bolt on mount



Main

| | |
|-----------------------|---------------------------|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 20 A |
| Voltage Rating | 120/240 V AC 120 V AC |
| Mounting Type | Bolt-on |
| Number of Poles | 1P |
| Circuit Breaker Type | Combination ARC-fault |
| Ratings | Not rated |
| Electrical Connection | Pressure plate |
| Connections Terminals | Pigtail neutral |

Complementary

| | |
|------------------------|--|
| Interrupt Rating | 22 KA 120/240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz |
| Number of Panel Spaces | 1 |
| Wire Size | AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium |
| Height | 4.76 in (121 mm) |
| Width | 0.75 in (19 mm) |
| Depth | 2.91 in (74 mm) |
| Net Weight | 0.56 lb(US) (0.254 kg) |

Environment

| | |
|----------------|------------------|
| Certifications | UL Listed CSA |
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 06303-QO SINGLE POLE ARC FAULT CIRCUIT BREAKER |
| Discount Schedule | DE2A |
| GTIN | 785901677918 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 8.96 oz (254.012 g) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.40 in (3.556 cm) |
| Package 1 width | 4.20 in (10.668 cm) |
| Package 1 Length | 5.60 in (14.224 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|