



### Main

Product or Component Type	Logic I/O card
Range Compatibility	Altivar Lift Altivar 71Q Altivar 61 Altivar 71 Altivar 61Q
Supply	Internal supply for reference potentiometer, 10.5 V DC 10...11 V) , <0.01 A 1...10 kOhm overload and short-circuit protection Internal supply, 24 V DC 21...27 V) , <0.2 A overload and short-circuit protection
Discrete output number	5
Discrete output type	R3A, R3B, R3C) configurable relay logic LO1, LO2) assignable logic 1.5...2.5 ms level 1 PLC
Discrete output logic	LO1, LO2) negative LO1, LO2) positive
Discrete input number	4
Discrete input type	LI7...LI10) programmable level 1 PLC 3.5 kOhm 1.5...2.5 ms
Discrete input logic	Negative LI7...LI10), $\geq 16$ V, $\leq 10$ V Positive LI7...LI10), $\leq 5$ V, $\geq 11$ V

### Complementary

Electrical durability	100000 cycles configurable relay logic
Discrete output voltage	24 V DC 12...30 V) assignable logic
Maximum output current	0.2 A, assignable logic
Minimum switching current	3 mA 24 V DC configurable relay logic
Maximum switching current	Configurable relay logic 2 A 250 V AC inductive, $\cos \phi = 0.4$ 7 ms Configurable relay logic 2 A 30 V DC inductive, $\cos \phi = 0.4$ 7 ms Configurable relay logic 5 A 250 V AC resistive, $\cos \phi = 1$ Configurable relay logic 5 A 30 V DC resistive, $\cos \phi = 1$
PTC probe input	TH1+, TH1- trip resistance 3 kOhm TH1+, TH1- reset resistance 1.8 Ohm TH1+, TH1- short circuit protection $< 0.05$ Ohm TH1+, TH1- for 6 PTC probe $\leq 1.5$ Ohm
Discrete input voltage	24 V DC $\leq 30$ V)programmable
Electrical connection	Terminal, 1.5 mm <sup>2</sup> / AWG 16, 2.21 lbf.in (0.25 N.m)
Net Weight	0.66 lb(US) (0.3 kg)

### Ordering and shipping details

Category	22135-ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	3389118067103
Nbr. of units in pkg.	1
Package weight(Lbs)	12.80 oz (363.0 g)
Returnability	No
Country of origin	ID

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.76 in (7 cm)
Package 1 width	6.69 in (17 cm)
Package 1 Length	9.06 in (23 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	6.66 lb(US) (3.021 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------