


# XVS72BMWP

Electronic alarm, Harmony XVS, white, PNP, mounting support DIN 72, 0...90 dB, 16 tones, 4 channels, 12...24 V DC



## Main

|                           |                  |
|---------------------------|------------------|
| Range of Product          | Harmony XVS      |
| Product or Component Type | Electronic alarm |
| Device short name         | XVS              |

## Complementary

|  |   |
|--|---|
| Color                                  | White   |
| Material                               | ABS (acrylonitrile butadiene-styrene) body<br>PC (polycarbonate) terminal cover |
| Net Weight                             | 0.40 lb(US) (0.18 kg)   |
| Marking                                | CE  |
| Overvoltage category                   | Class II EN/IEC 61140   |
| Mounting Support                       | 72 mm DIN rail  |
| [Us] rated supply voltage              | 12...24 V DC  |
| [Uimp] rated impulse withstand voltage | 0.8 kV  |
| Current consumption                    | 117 mA 12 V<br>125 mA 24 V<br>158 mA 12 V<br>200 mA 24 V                        |
| Clamping Connection Capacity           | <= 1 x 1.5 mm <sup>2</sup>  |
| Width                                  | 2.83 in (72 mm)   |
| Height                                 | 2.83 in (72 mm)   |
| Depth                                  | 2.73 in (69.3 mm)   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Discrete output type                  | PNP  |
| Signalling type                       | 16 tones alarm                                 |
| Standards                             | EN/IEC 61000-6-3<br>EN/IEC 61000-6-2<br>UL 464 |
| Product Certifications                | UR   |
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -31...158 °F (-35...70 °C)                     |
| Ambient Air Temperature for Operation | 14...122 °F (-10...50 °C)                      |
| IP degree of protection               | Panel mounted IP54 EN/IEC 60529                |
| Noise level                           | 0...90 dB continuous or intermittent tone) 1 m |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 22617-XVC TOWER LIGHTS |
| Discount Schedule     | XV                     |
| GTIN                  | 3606480032912          |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 9.35 oz (265.0 g)      |
| Returnability         | No                     |
| Country of origin     | ID                     |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 4.13 in (10.5 cm)       |
| Package 1 width              | 3.66 in (9.3 cm)        |
| Package 1 Length             | 3.74 in (9.5 cm)        |
| Unit Type of Package 2       | P06                     |
| Number of Units in Package 2 | 16                      |
| Package 2 Weight             | 27.91 lb(US) (12.66 kg) |
| Package 2 Height             | 30.31 in (77 cm)        |
| Package 2 width              | 31.50 in (80 cm)        |
| Package 2 Length             | 23.62 in (60 cm)        |
| Unit Type of Package 3       | S03                     |
| Number of Units in Package 3 | 16                      |
| Package 3 Weight             | 11.38 lb(US) (5.164 kg) |
| Package 3 Height             | 11.81 in (30 cm)        |
| Package 3 width              | 11.81 in (30 cm)        |
| Package 3 Length             | 15.75 in (40 cm)        |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

