



## Overview

Lead time	Usually in Stock
-----------	------------------

## Main

Rated power in W	390 W
Rated power in VA	650 VA
Nb of power socket outlets	4 NEMA 5-15R 4 NEMA 5-15R surge
Main Output Voltage	120 V
Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	5 ft (1.52 m)
Number of cables	1

## General

Provided equipment	User Manual USB cable
Max runtime	62 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Color	Black
Depth	11.89 in (30.2 cm)
Height	3.46 in (8.8 cm)
Mounting preference	No preference
Net weight	13.67 lb(US) (6.2 kg)
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Width	7.09 in (18 cm)

## Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	90...140 V
Maximum Input Current per Phase	12 A

## Output

Max Configurable Power (Watts)	390 W
Output Frequency (sync to mains)	60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum output current	12 A
Maximum configurable power in VA	650 VA
Transfer Time	8ms typical : 12ms maximum

## Conformance

Product certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) NOM TÜV-C
Standards	CSA C22.2 No. 107.1 FCC Part 15 class B FCC part 68 UL 1778
Equipment protection policy	Lifetime : \$75000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA

## Batteries & Runtime

Battery type	Lead-Acid battery
Typical recharge time	24 h
RBC Quantity	1
Battery Voltage	12 V
Battery capacity	9.0 Ah
Battery Charge Power (Watts)	3 W rated
Battery power in VAh	79 VAh runtime
Battery life	2...5 year(s)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

## Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm

## Surge Protection and Filtering

Surge energy rating	340 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
Data line protection	RJ45 10/100 Base-T Ethernet protection
Let Through Voltage Rating	330 V







## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304285434
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

## Packing Units

Package 1 Height	5.04 in (12.8 cm)
Package 1 width	9.25 in (23.5 cm)
Package 1 Length	15.47 in (39.3 cm)
SCC14	10731304285431
Number of Units in Package 2	2
Package 2 Weight	31.68 lb(US) (14.37 kg)
Package 2 Height	10.39 in (263.91 mm)
Package 2 width	11.1 in (281.94 mm)
Package 2 Length	15.9 in (403.86 mm)
Number of Units in Package 3	48
Pallet unit layers	20
Pallet layers	5

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Energy Star	 <a href="#">ENERGY STAR UPS V2.0 (USA)</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------