



SKU: CLND-6-12-134

UPC: 0783669630145

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 6, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-24
ILSCOs Die Index Number	I-24
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.125
Barrel Length (mm)	28.575
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	0.399
Height BX (IN)	2.25
Height (mm)	10.1346
Inside Diameter (IN)	0.225
Inside Diameter (mm)	5.715
Length (IN)	4.32
Length (mm)	109.728
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	0.313
Outside Diameter (mm)	7.9502
Strip Length (mm)	30.1498
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.087
Tang Thickness (mm)	2.2098

Tang Width (IN)	0.755
Tang Width (mm)	19.177
Weight (LB)	0.0644465111631894
Weight BX (LB)	3.7803
Width (IN)	0.755
Width BX (IN)	5
Width (mm)	19.177

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	6 G,H,I,K,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963014

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	Blue

Voltage

Voltage Rating	35 kV
----------------	-------