



## 5225-W

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, White

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, - White

- Functional – provides multiple controls in a single-gang space
- Durable – impact-resistant thermoplastic nylon construction
- Compatible – designed for use with Leviton traditional wallplates

Color :  White

UPC Code : 078477965849

Country Of Origin : Mexico

NEMA :  5-15R

### Available Colors :



### Technical Information

#### AC Horsepower Ratings

**HP Rating :** 1/2HP-120V

**Max. Amperage :** 12 Amp

#### Electrical Specifications

**Dielectric Voltage :**  
Withstands 1500V for 1 minute

**Grounding :** Grounding

**Overload UL20 Test :** 100 cycles of OL at 4.8 times rated current

**Pole :** 1

**Receptacle Amperage :** 15 Amp

**Receptacle Voltage :** 125V AC

**Switch Amperage :** 15 Amp

**Switch Voltage :** 120V AC

**Temperature Rise :** Maximum 30 degrees C rise

#### Environmental Specifications

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40° C to 65° C

#### Material Specifications

**Actuator Material :** Thermoplastic

**Body Material :** Thermoplastic

**Color :** White

**Strap Material :** Steel

#### Mechanical Specifications

**Product ID :** Stamped on Strap

**Terminal Accom. :** 14-12 AWG

**Terminal ID :** Brass-Hot Black-Hot White-Neutral Green-Gnd

**Termination :** Side

**Torque Range :** 14 – 18 in.-lbs

#### Product Features

**Amperage :** 15 A

**Color :** White

**Feature :** Single-Pole / 5-15R

**NEMA :** 5-15R

**Product Type :** Switch/Outlet Combo

**Type** : Duplex Style  
Combination Switch

**Voltage** : 120 VAC

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 111** : File  
#152105

**NEMA** : WD-1 & WD-6

**NOM** : 057

**UL Standard** : UL 20

**Warranty** : 2-Year Limited

**Features and Benefits**

- AC quiet switches have silver-cadmium oxide contacts and receptacles have double-wipe contacts for maximum conductivity
- All devices have grounding screw
- Side wired with terminal screws that accept up to #12 copper or copper-clad wire
- Fit standard wallboxes
- Break-off tabs on devices with AC quiet switches permit conversion to separate feeds
- Backed by a Limited Two-Year Warranty

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	<input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

