

YH2929WC, Cu Compression H Tap and Cover, 250 kcmil-2 AWG Run and Tap

By Burndy
Catalog # YH2929WC



Copper Compression H Tap, Tin Plated, Accommodating the following wire sizes - Run (Main): 250 kcmil-2 AWG Class B,C, 4/0 AWG-2 AWG Class I, DLO; Tap 1: 250 kcmil-2 AWG Class B,C, 4/0 AWG-2 AWG Class I, DLO, kitted with black cover See sale drawing for metric wire size accommodates

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

General

Catalog Number	YH2929WC
Color Code	Purple
Connector Type	H-TAP W/BLK COVER
Die Index	654
EU RoHS Indicator	Yes
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	CRIMPIT
Temperature Rating	194
Trade Name	CRIMPIT™
Type	Compression Taps
UPC	781810000281
UPC 12 Digit	7818100002811

Dimensions

Dimension - L Length Overall	23 mm
mm	

Dimension - Length Overall	0.90 in
inch	

Dimension - Strip Length inch	1-1/16
-------------------------------	--------

Dimension - Width inch	1.85 in
------------------------	---------

Electrical Ratings

Voltage - Maximum	35000
-------------------	-------

Voltage Rating	35 kV
----------------	-------

Conductor Related

Conductor - Copper Flex G Run	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex G Tap	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex H Tap	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex I Run	4/0 AWG-2 AWG
-------------------------------	---------------

Conductor - Copper Flex I Tap	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex I Tap	4/0 AWG-2 AWG
Range	

Conductor - Copper Flex K Run	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex K Tap	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex M Run	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Flex M Tap	2;1;1/0;2/0;3/0;4/0
-------------------------------	---------------------

Conductor - Copper Str Run	2;1;1/0;2/0;3/0;4/0;250
----------------------------	-------------------------

Conductor - Copper Str Run	250 KCMIL-2 AWG
Range	

Conductor - Copper Str Tap	2;1;1/0;2/0;3/0;4/0;250
----------------------------	-------------------------

Conductor - Copper Str Tap	250 KCMIL-2 AWG
----------------------------	-----------------

Range	
-------	--

Conductor - Material	COPPER
----------------------	--------

Conductor Type	CODE/FLEX
----------------	-----------

Certifications And Compliance

Buy American Compliant	Yes
------------------------	-----

Certification - CSA Approved	Yes
------------------------------	-----

Certification - ETL	No
---------------------	----

Certification - UL Recognized	No
-------------------------------	----

Certification - cULus	No
-----------------------	----

Industry Standard(s)	UL 486A-486B
----------------------	--------------

Standards - RoHS Compliance	CM
-----------------------------	----

Status	
--------	--

UL Listed Yes

Logistics

Carton Quantity 25
Minimum Pack Quantity 1
Pallet Quantity 2250

Catalogs - BURNDY Master Catalog - Section C - Compression Connections
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - SD..206566-01
Specifications - YH2929WC

Product Assets

