



# UC4W28, Copper Parallel Groove Clamp

By Burndy  
Catalog # [UC4W28](#)



CU Parallel Groove Clamp accommodates large number of CU Conductors, Conductor: 4 Sol. - 4/0 Str. (Either Groove).

## Application

For Range Of Copper

## General

EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	240 LBS/in
Plated	N
Plating Type	Unplated
Sub Brand	TAPIT
Type	UC
UPC	781810012888

## Dimensions

Dimension - B Length fraction	2-1/8 in
Dimension - B Length inch	2.125 in
Dimension - Height fraction	1-15/16 in
Dimension - Height inch	1.93 in
Dimension - Width fraction	1-3/4 in

## Conductor Related

Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Size A	4 - 4/0
Conductor - Copper Str Size A Range	4 - 4/0
Conductor - Copper Str Size B	4 - 4/0
Conductor - Copper Str Size B Range	4 - 4/0
Conductor - Copper Str Size	4 AWG-4/0 AWG
Conductor - Copper Str Size Range	4 AWG-4/0 AWG

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

## Logistics

Minimum Pack Quantity	2
-----------------------	---

## Product Assets

[3D Models - UC4W28\\_MODEL-STEP](#)  
[3D Models - UC4W28\\_MODEL-IGES](#)  
[3D Models - UC4W28\\_MODEL-PDF](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - SA..038990-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-UC4W28-SPEC-EN | REV 1/2024