

YCHC29TC29, Cu Compression C Tap, 250 kcmil-2 AWG Run and Tap



By Burndy
Catalog # YCHC29TC29

Copper Compression C Tap, 250 kcmil- 2 AWG (Main), 250 kcmil- 2 AWG (Tap), Tin Plated.

Features

- Range taking C-tap that allows for less inventory as one C-tap can accommodate a multitude of wire combinations
- Manufactured from high conductivity wrought copper providing low resistance for excellent electrical conductivity
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping

Application

Wire Tap

General

Catalog Number	YCHC29TC29
Color Code	Orange
Connector Type	C-TAP
Die Index	997
EU RoHS Indicator	Yes
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	CRIMPIT
Trade Name	CRIMPIT™
Type	YCHC Series
UPC	781810013717
UPC 12 Digit	7818100137177

Dimensions

Dimension - Height inch	2.12 in
Dimension - L Length Overall mm	24 mm
Dimension - Length Overall inch	0.94 in
Dimension - Strip Length inch	1 in
Dimension - Width inch	0.98 in

Electrical Ratings

Voltage - Maximum	35000
-------------------	-------

Conductor Related

Conductor - Copper Flex I Run	2 AWG-4/0 AWG Range
Conductor - Copper Flex I Tap	2 AWG-4/0 AWG Range
Conductor - Copper Flex K Run	2 AWG-4/0 AWG Range
Conductor - Copper Flex K Tap	2 AWG-4/0 AWG Range
Conductor - Copper Flex M Run	2 AWG-4/0 AWG Range
Conductor - Copper Flex M Tap	2 AWG-4/0 AWG Range
Conductor - Copper Str Run	250 KCMIL-2 AWG
Conductor - Copper Str Run	250 KCMIL-2 AWG
Conductor - Copper Str Tap	250 KCMIL-2 AWG
Conductor - Copper Str Tap	250 KCMIL-2 AWG
Conductor - Material	COPPER
Conductor Size	250 KCMIL-250 KCMIL
Conductor Type	CODE/FLEX

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Carton Quantity	24
Minimum Pack Quantity	1
Pallet Quantity	9408

Product Assets

- [3D Models - YCHC29TC29_MODEL-IGES](#)
- [3D Models - YCHC29TC29_MODEL-STEP](#)
- [3D Models - YCHC29TC29_MODEL-PDF](#)

Catalogs - BURNDY Master Catalog - Section C - Compression
Connections
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - SD..206624-01
Specifications - YCHC29TC29



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
BRDY-YCHC29TC29-SPEC-EN | REV 10/2024