

YDS4CA, Aluminum Full Tension Splice, Staked Cable Stop

By Burndy
Catalog # [YDS4CA](#)



Full tension aluminum splice with staked in cable stop. ANSI C199.4 Class 1 (Full Tension), Die Index: 162, 2-5/8 L.

Application

For All Aluminum Compressed And Compact Conductors

General

Color Code	Orange
Connector Type	Splice
Die Index	162
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS-A
UPC	781810015377

Dimensions

Dimension - B Length inch	1.25 in
Dimension - Inside Diameter inch	0.24 in
Dimension - L Length Overall mm	67 mm
Dimension - Length Overall inch	2.62 in
Dimension - Outside Diameter inch	0.4 in

Conductor Related

Conductor - AAAC 5005 Size	48.69 (7) kcmil
Conductor - AAAC 5005 Size Range	48.69 (7) kcmil
Conductor - AAAC 6201 Size	48.69 (7) kcmil
Conductor - AAAC 6201 Size Range	48.69 (7) kcmil
Conductor - ACAR Str Size	4 (7) AWG
Conductor - ACAR Str Size Range	4 (7) AWG
Conductor - ACSR Cmpt Size	4 AWG
Conductor - ACSR Cmpt Size Range	4 AWG
Conductor - AL Str Size	4 AWG
Conductor - AL Str Size Range	4 AWG
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	29600

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Sales Drawings - SC019521-01](#)