



# KSA4, Aluminum Split Bolt Connector, Tin Plated

By Burndy  
Catalog # [KSA4](#)



Aluminum Split Bolt, (Run, Tap):: Al-Al: 4 AWG (Str), 4 AWG (Str) , Al-Cu: 8 AWG (Sol), 10 AWG (Sol) , Cu-Cu: 4 AWG (Str), 10 AWG (Sol), Tin Plated.

## Application

For All Combinations Of Aluminum To Aluminum, Aluminum To Copper And Copper To Copper, Aluminum Alloy Tin Plated

## General

Connector Type	Split Bolt
EU RoHS Indicator	Yes
Hardware Type	5/8-18 UNF
Installation Torque Recommended in-lb	165 LBS/in
Material	Aluminum
Plated	Y
Plating Type	Tin
Sub Brand	TRITAP, SERVIT
Temperature Rating	194
Trade Name	TRITAP™ SERVIT®
Type	KSA
UPC	781810015407
UPC 12 Digit	7818100154077

## Dimensions

Dimension - B Length fraction	1-1/9 in
Dimension - B Length inch	1.06 in
Dimension - Bolt Size inch	0.63 in
Dimension - Cross Flats inch	0.81 in
Dimension - Height fraction	5/7 in
Dimension - Height inch	0.71 in
Dimension - L Length Overall mm	35 mm
Dimension - Length Overall inch	1.38 in
Dimension - Width inch	0.62 in

## Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

## Conductor Related

Conductor - AL Str Run	8 AWG;6 AWG;4 AWG
Conductor - AL Str Run Range	8 AWG-4 AWG
Conductor - AL Str Tap	8 AWG;6 AWG;4 AWG
Conductor - AL Str Tap Range	8 AWG-4 AWG
Conductor - Copper Solid Run	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Solid Run Range	8 AWG-4 AWG
Conductor - Copper Solid Tap	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Solid Tap Range	10 AWG-4 AWG
Conductor - Copper Str Run	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Str Run Range	8 AWG-4 AWG
Conductor - Copper Str Tap	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Str Tap Range	10 AWG-4 AWG
Conductor Size	10-4 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Run</li> <li>• CU C Str-Run</li> <li>• CU C Solid-Run</li> <li>• AL C Str-Tap</li> <li>• CU C Str-Tap</li> <li>• CU C Solid-Tap</li> </ul>

## Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	100
-----------------	-----

Minimum Pack Quantity 1  
Pallet Quantity 46400

**Product Assets**

[3D Models - KSA4\\_MODEL-PDF](#)  
[3D Models - KSA4\\_MODEL-IGES](#)  
[3D Models - KSA4\\_MODEL-STEP](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - sd084189](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-KSA4-SPEC-EN | REV 1/2024