



Uninsulated Ring Terminal For 12 - 10 AWG

By Burndy
Catalog # [YAV10L36](#)



Copper Terminal, Ring Tongue w/ Inspection Hole, Wire Range 12-10 AWG, #8-#10 Stud, Tin Plated, Wire strip length: 7/16".

Application

For Use On Copper Commercial (Code) Cable, Type AN Aircraft Cable And Extra Flexible Conductors, Industrials, Hospitals, Electric Utilities, Shipboard And Marine, Computers, Steel Mills, Mining Equipment And Other Equipment That Is Subject To Vibration Or Requiring Dependable Electrical Performance

General

| | |
|--------------------------------------|---|
| Connector Type | Ring Terminal |
| EU RoHS Indicator | Yes |
| Feature - Barrel Style | Chamfered |
| Feature - Barrel Type | Standard |
| Material | Copper |
| Material Composition | <ul style="list-style-type: none"> • DLP Copper • Tin Plating |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Tongue Type | Ring |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| Sub Brand | HYLUG |
| Trade Name | HYLUG™ |
| Type | Ring Tongue |
| UPC | 781810025161 |

Dimensions

| | |
|---------------------------------|---------|
| Dimension - Bolt Size fraction | #8 |
| Dimension - D inch | 0.30 in |
| Dimension - Hole Size fraction | 1/5 |
| Dimension - Hole Size inch | 0.19 in |
| Dimension - Hole Size mm | 5 mm |
| Dimension - L Length Overall mm | 22 mm |
| Dimension - Length Overall inch | 0.86 in |
| Dimension - N inch | 0.16 in |
| Dimension - Pad Width inch | 0.29 in |
| Dimension - Stud Size inch | #8 |
| Dimension - Z inch | 0.23 in |

Conductor Related

| | |
|-------------------------------------|--|
| Conductor - Copper Solid Size | 12;11;10 |
| Conductor - Copper Solid Size Range | 12-10 |
| Conductor - Copper Str Size | 12;10 |
| Conductor - Copper Str Size Range | 12-10 |
| Conductor Size | 12 - 10 AWG |
| Conductor Type | <ul style="list-style-type: none"> • CU C Solid-Size • CU C Str-Size |

Certifications and Compliance

| | |
|------------------------------------|-------|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL467 |
| Standards - Industry Standards Met | UL486 |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|-------|
| Carton Quantity | 500 |
| Minimum Pack Quantity | 500 |
| Pallet Quantity | 99999 |

Product Assets

- [3D Models - YAV10L36_MODEL-PDF](#)
- [3D Models - YAV10L36_MODEL-STEP](#)
- [3D Models - YAV10L36_MODEL-IGES](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Sales Drawings - 50094160](#)
- [Technical Solutions - BURNDY_YAV10L36_Specsheet](#)



A proud member of the Hubbell Family.

