



GC2525CT, Mechanical Grounding Connector, 2 Cables to Bar

By Burndy
Catalog # GC2525CT



Cast Copper Alloy Cable Tray Ground Clamp, #6 Sol. (.162 Dia.)
-1/0 Str. (.372 Dia.), 1.12 in L, 1.45 in W, Tin Plated.

Application

For Direct Burial Applications In Concrete Or Earth And For Used With Aluminum Or Galvanized Steel Cable Tray

General

EU RoHS Indicator	Yes
Installation Torque	240 lb-in
Recommended in-lb	
Material	Copper Alloy
Plated	Y
Plating Type	Tin
Sub Brand	MECHANICAL CONNECTOR
Type	GC-CT
UPC	781810035504
UPC 12 Digit	7818100355044

Dimensions

Dimension - B Length inch	1.12 in
Dimension - Cross Flats inch	0.56 in
Dimension - Height inch	1.95 in
Dimension - Width inch	1.45 in
Dimension - Width mm	37 mm

Conductor Related

Conductor - AL Str Size	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG
Conductor - AL Str Size Range	6 AWG-1/0 AWG
Conductor - Copper Solid Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Size Range	6 AWG-1/0 AWG
Conductor - Copper Str Size	7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0
Conductor - Copper Str Size Range	7 AWG - 1/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

- [3D Models - GC2525CT_MODEL-IGES](#)
- [3D Models - GC2525CT_MODEL-STEP](#)
- [3D Models - GC2525CT_MODEL-PDF](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Sales Drawings - sc082752-01](#)



A proud member of the Hubbell Family.

