




YHD3, Line Tap Connector, AL-CU, AL-AL

By Burndy
Catalog # YHD3

Compression Line Tap Connector for Aluminum to Copper and Aluminum to Aluminum applications, 1.47 H, 1.88 L, .76 W.



Application

For Accommodate Combinations Of Aluminum To Copper, And Aluminum To Aluminum Conductors

General

Die Index	D3
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	LOKTAP
Trade Name	LOKTAP™
Type	YHD
UPC	781810139066

Dimensions

Dimension - Height fraction	1-47/100 in
Dimension - Height inch	1.47 in
Dimension - L Length Overall mm	48 mm
Dimension - Length Overall inch	1.88 in
Dimension - Width fraction	19/25 in
Dimension - Width inch	0.76 in
Dimension - Width mm	19 mm

Conductor Related

Conductor - ACSR Cmpt Run	2/0 AWG;3/0 AWG
Conductor - ACSR Cmpt Run Range	2/0 AWG-3/0 AWG
Conductor - ACSR Cmpt Tap	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - ACSR Cmpt Tap Range	6 AWG-1 AWG
Conductor - ACSR Str Run	1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Run Range	1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG;5 (6/1) Thrush AWG;4 (6/1) Swan AWG;4 (7/1) Swanate AWG;3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG
Conductor - ACSR Str Tap Range	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - AL Str Run	2/0 AWG;3/0 AWG
Conductor - AL Str Run Range	2/0 AWG-3/0 AWG
Conductor - AL Str Tap	6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Tap Range	6 AWG-2 AWG
Conductor - Copper Solid Run	3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Solid Tap	#6;5 AWG;4 AWG;3 AWG;2 AWG;1/0
Conductor - Copper Solid Tap Range	#6-1/0
Conductor - Copper Str Run	2/0 AWG;3/0 AWG
Conductor - Copper Str Run Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Tap	LOKTAP™ Compression Line Tap Connector for Aluminum to Copper and Aluminum to Aluminum applications

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	250
Minimum Pack Quantity	25

Product Assets

[3D Models - YHD3_MODEL-STEP](#)
[3D Models - YHD3_MODEL-PDF](#)
[3D Models - YHD3_MODEL-IGES](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Sales Drawings - sd206084-01](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YHD3-SPEC-EN | REV 8/2023