



YSS2R, Single Aluminum Sleeve

By Burndy
Catalog # [YSS2R](#)

Single aluminum sleeve designed for service drop or short span overhead distribution lines, Die index: BG or 5/8.



Application

For Aluminum, ACSR, 6201, 5005 And Compressed Conductors And Service Drop Or Short Span Overhead Distribution Lines

General

Color Code	Red
Connector Type	Splice
Die Index	BG or 5/8
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YSS
UPC	781810169551
UPC 12 Digit	7818101695511

Dimensions

Dimension - B Length fraction	1-39/50 in
Dimension - B Length inch	1.78 in
Dimension - L Length Overall mm	96 mm
Dimension - Length Overall inch	3.78 in
Dimension - Outside Diameter inch	0.65 in

Conductor Related

Conductor - ACSR Str Size	2 (6/1) Sparrow AWG; 2 (7/1) Sparate AWG
Conductor - ACSR Str Size Range	2 (6/1) Sparrow AWG-2 (7/1) Sparate AWG
Conductor - AL Str Size	2 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	50
Minimum Pack Quantity	1
Pallet Quantity	14800

Product Assets

[3D Models - YSS2R_MODEL-STEP](#)
[3D Models - YSS2R_MODEL-PDF](#)
[3D Models - YSS2R_MODEL-IGES](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - sc031169-01](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YSS2R-SPEC-EN | REV 8/2023