

Underground Connector Splice Kit

By Burndy
Catalog # UGSKIT250



Watertight Underground Splice Kit, 1 AWG-250 kcmil, w/ Two Heavy Wall Heat Shrink Sleeves, Al/Cu Rated.

Application

For All Aluminum or Copper/Aluminum Combinations, UF Direct Burial

General

Connector Type	Splice/Heat Shrink Kit
EU RoHS Indicator	Yes
Hex Size	5/16
Material	Aluminum
Physical Attribute - Screw Type	Allen
Plated	N
Plating Type	Unplated
Sub Brand	SPLICE KIT
Temperature Rating	194
Type	UGSKIT, Watertight/Underground
UPC	781810175286

Dimensions

Dimension - L Length Overall mm	102 mm
Dimension - Length Overall inch	4.00 in

Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

Conductor Related

Conductor - AL Str Size	1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - AL Str Size Range	1 AWG-250 kcmil
Conductor - Copper Str Size	1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Size Range	1 AWG-250 kcmil
Conductor Size	1 AWG-250 KCMIL

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL486D
Standards - Industry Standards Met	UL486D
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

- [3D Models - UGSKIT250_MODEL-PDF](#)
- [3D Models - UGSKIT250_MODEL-IGES](#)
- [3D Models - UGSKIT250_MODEL-STEP](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Sales Drawings - SD..211382-01](#)