

AMS250, AL Set Screw Splice, 250 kcmil-6 AWG, 4 Screws, Al/Cu Rated

By Burndy
Catalog # [AMS250](#)



Aluminum Mechanical Splice, 250 kcmil-6 AWG, 5/8" Screw Dia, 4 Screws, 5/16" Hex Size, Al/Cu Rated, Tin Plated.

Application

For Use With Copper And Aluminum Conductors

General

Catalog Number	AMS250
Connector Type	In-Line
EU RoHS Indicator	Yes
Hex Size	5/16
Installation Torque	50 LBS/in
Recommended In-lb	
Material	Aluminum
Material - Hardware	Aluminum
Physical Attribute - Number of Screws	4
Physical Attribute - Screw Type	Allen
Plated	Y
Plating Type	Tin
Sub Brand	SPLICER/REDUCER
Temperature Rating	194° F
Type	AMS, Dual Rated
UPC	781810241035
UPC 12 Digit	7818102410355

Dimensions

Dimension - H1 Height inch	1.09 in
Dimension - Height fraction	1-3/32
Dimension - Height mm	0 mm
Dimension - L Length Overall mm	104 mm
Dimension - Length Overall inch	4.09 in
Dimension - Width fraction	1 in
Dimension - Width inch	1.00 in
Dimension - Width mm	25 mm

Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

Conductor Related

Conductor - AL Str Run	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0
------------------------	---

Conductor - AL Str Run Range	AWG;4/0 AWG;250 kcmil 6 AWG-250 kcmil
Conductor - AL Str Size	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Size Range	6 AWG-4/0 AWG
Conductor - AL Str Tap	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - AL Str Tap Range	6 AWG-250 kcmil
Conductor - Copper Solid Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	6 AWG-4/0 AWG
Conductor - Copper Solid Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	4 AWG-4/0 AWG
Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Tap Range	6 AWG-4/0 AWG
Conductor - Copper Str Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Run Range	6 AWG-250 kcmil
Conductor - Copper Str Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Size Range	6 AWG-250 kcmil
Conductor - Copper Str Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil

Conductor - Copper Str Tap 6 AWG-250 kcmil
Range
Conductor Size 6 AWG-250 KCMIL

Certifications And Compliance

Buy American Compliant Yes
Certification - CSA Approved Yes
Certification - UL Listed Direct No
Burial
Industry Standard(s) UL467
Standards - Industry Standards UL467
Met
Standards - RoHS Compliance EX
Status
UL Listed Yes

Logistics

Carton Quantity 120
Minimum Pack Quantity 1

Product Assets

[3D Models - AMS250_MODEL-PDF](#)
[3D Models - AMS250_MODEL-STEP](#)
[3D Models - AMS250_MODEL-IGES](#)
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_AMS_Lineart](#)
[Sales Drawings - sd207208-01](#)
[Specifications - AMS250](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
BRDY-AMS250-SPEC-EN | REV 10/2024