



# GAR3902TC, Mechanical Ground Connector, For 2 Hole Lug to Pipe or Rod

By Burndy  
Catalog # [GAR3902TC](#)



Mechanical Grounding Connector, For 2 Hole Lug to Water Pipe or Rod, 1/2" - 1" Pipe, 3/8" Stud.

## Application

For Direct Burial, Water Pipe As Well As Structural And Reinforcing Rod Shapes

## General

EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	240 LBS/in
Material	Copper Alloy
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Number of Holes	3
Physical Attribute - Pad Configuration	2.50 x 2.50 - 3 Holes
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Type	Rod or Tube Clamp with Mounting Pad
U Bolt Type	1031
UPC	781810241103
UPC 12 Digit	7818102411033

## Dimensions

Dimension - Bolt Size fraction	3/8
Dimension - Height inch	3.50 in
Dimension - Length Overall inch	2.50 in
Dimension - Outside Diameter inch	1.32 in
Dimension - Thread Size	3/8-16
Dimension - Threads per inch	16
Dimension - Width inch	3.75 in
Dimension - Width mm	95 mm

## Conductor Related

Conductor - Copper Tube EH Size	1/2;1
Conductor - Copper Tube EH Size Range	1/2-1
Conductor - Pipe or Round Tube Size	0.5 - 1 in

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - se..206158-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-GAR3902TC-SPEC-EN | REV 1/2024