



# HSIC10500FR, Heavy Wall Cross-Linked Black Polyolefin Heat Shrinkable End Cap, 1/0-500 kcmil Code, #1-313 kcmil Flex, 600 V, Fire Retardant.

By Burndy  
Catalog # [HSIC10500FR](#)



Heavy Wall Cross-Linked Black Polyolefin Heat Shrinkable End Cap, 1/0-500 kcmil Code, #1-313 kcmil Flex, 600 V, Fire Retardant.

## Application

For Used To Insulating Exposed Conductors In Energized Applications

## General

Color	Black
Connector Type	HEAVY WALL END CAP
EU RoHS Indicator	Yes
Material	Cross-linked Polyolefin
Sub Brand	HEAT SHRINK
Type	HSIC-FR, Heavy Wall, Fire Retardant
UPC	781810266557

## Conductor Related

Conductor Range	ConductorRange
Conductor Size	1/0AWG - 500kvmil

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

- [Catalogs - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Sales Drawings - SC209680-01](#)
- [Video - Heat Shrink Product Overview & Installation](#)



A proud member of the Hubbell Family.