


# Compression Terminal

By Burndy  
Catalog # YA39A3

AL Terminal, AL9CU, Internal Chamfer, Tin Plated, Prefilled PENETROX™ A13, End Cap, UL/CSA, 90°C, Up to 35kV, Color Code, Die Index.



## Application

Wire Termination

## General

|                                      |                      |
|--------------------------------------|----------------------|
| Color Code                           | Yellow               |
| Connector Type                       | DUAL RATED           |
| Die Index                            | 936                  |
| EU RoHS Indicator                    | Yes                  |
| Feature - Barrel Style               | Chamfered            |
| Feature - Barrel Type                | Standard             |
| Finish Type                          | Tin-Plated           |
| Material                             | ALUMINUM             |
| Physical Attribute - Number of Holes | 1                    |
| Physical Attribute - Tongue Type     | Standard             |
| Plated                               | Y                    |
| Plating Type                         | Tin - Electro Plated |
| Sub Brand                            | HYLUG                |
| Temperature Rating                   | 194                  |
| Trade Name                           | HYLUG™               |
| Type                                 | YA-A, Dual Rated     |
| UPC                                  | 781810752067         |
| UPC 12 Digit                         | 7818107520677        |

## Dimensions

|                                   |           |
|-----------------------------------|-----------|
| Dimension - B Length fraction     | 2-7/16 in |
| Dimension - B Length inch         | 2.46 in   |
| Dimension - Bolt Hole Size inch   | 0.66 in   |
| Dimension - Bolt Size fraction    | 5/8       |
| Dimension - Bolt Size inch        | 0.63      |
| Dimension - D inch                | 1.88 in   |
| Dimension - Hole Size fraction    | 5/8       |
| Dimension - Hole Size inch        | 0.69      |
| Dimension - Hole Size mm          | 17.5 mm   |
| Dimension - L Length Overall mm   | 147 mm    |
| Dimension - Length Overall inch   | 5.80 in   |
| Dimension - N inch                | 0.88 in   |
| Dimension - Outside Diameter inch | 1.46 in   |
| Dimension - Pad Width inch        | 2.05 in   |
| Dimension - Strip Length inch     | 2 7/8     |
| Dimension - Strip Length mm       | 73        |

## Electrical Ratings

|                   |       |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating    | 35 kV |

## Conductor Related

|                                   |                       |
|-----------------------------------|-----------------------|
| Conductor - AL Str Size           | 700 KCMIL-750 KCMIL   |
| Conductor - AL Str Size Range     | 700 kcmil - 750 kcmil |
| Conductor - Copper Str Size       | 700 KCMIL;750 KCMIL   |
| Conductor - Copper Str Size Range | 700 kcmil - 750 kcmil |
| Conductor - Material              | ALUMINUM / COPPER     |
| Conductor Size                    | 700 KCMIL;750 KCMIL   |
| Conductor Type                    | CODE                  |
| Wire Size                         | 700 KCMIL;750 KCMIL   |

## Certifications and Compliance

|                                    |              |
|------------------------------------|--------------|
| Certification - CSA Approved       | Yes          |
| Certification - ETL                | No           |
| Certification - UL Recognized      | No           |
| Certification - cULus              | No           |
| Industry Standard(s)               | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM           |
| UL Listed                          | Yes          |

## Logistics

|                       |   |
|-----------------------|---|
| Carton Quantity       | 3 |
| Minimum Pack Quantity | 1 |

## Product Assets

[Customer Notices - Prop 65 Notice](#)  
[Installation Manuals - Aluminum Installation Instructions](#)  
[Sales Drawings - SD073935-01](#)

|                                   |          |
|-----------------------------------|----------|
| Dimension - Stud Size fraction    | 5/8      |
| Dimension - Stud Size inch        | 5/8      |
| Dimension - Thread Size           | 5/8 in   |
| Dimension - Z inch                | 1.00 in  |
| Physical Attribute - Tongue Angle | Straight |



**A proud member of the Hubbell Family.**

©2023 Hubbell Incorporated. All rights reserved.  
BRDY-YA39A3-SPEC-EN | REV 8/2023