

# YCA321RL2N

By Burndy  
Catalog # YCA321RL2N

Aluminum compression lug designed for terminating overhead conductors to switch pads and other substation switch yard apparatus, Die index: 655.



## Application

Used for terminating overhead conductors to switch pads and other substation or switch yard apparatus.

## General

Connector Type	Terminal
Die Index	655
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINALS, HYLUG
Trade Name	HYLUG™
Type	YCA-RL-2N
UPC	781810810743
UPC 12 Digit	7818108107433

## Dimensions

Dimension - B Length inch	2.25 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	165 mm
Dimension - Length Overall inch	6.50 in
Dimension - Outside Diameter inch	1.13 in
Dimension - Pad Width inch	1.59 in

## Conductor Related

Conductor - ACSR Cmp Size Range	336.4 kcmil
Conductor - ACSR Str Size	336.4 (18/1) Merlin kcmil
Conductor - AL Str Size	336 kcmil
Conductor Type	<ul style="list-style-type: none"> <li>• ACSR C Str-Size</li> <li>• AAC</li> </ul>

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	10
Minimum Pack Quantity	1
Pallet Quantity	3920

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - SD052276-01](#)