



YCS25R, Aluminum Sleeve, Staked Cable Stop

By Burndy
Catalog # [YCS25R](#)



HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 7-1/8 IN L.

Application

For ACSR, All Aluminum, 6201, 5005 And Compressed Conductors

General

Connector Type	Splice
Die Index	243
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YCS-R
UPC	781810820513
UPC 12 Digit	7818108205133

Dimensions

Dimension - B Length inch	3.48 in
Dimension - L Length Overall mm	180 mm
Dimension - Length Overall inch	7.09 in
Dimension - Outside Diameter inch	0.62 in

Conductor Related

Conductor - ACSR Str Size	1/0 (6/1) Raven AWG
Conductor - ACSR Str Size Range	1/0 (6/1) Raven AWG
Conductor - AL Str Size	1/0 (7, 19) AWG
Conductor - AL Str Size Range	1/0 (7, 19) AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	9800

Product Assets

[3D Models - YCS25R_MODEL-STEP](#)
[3D Models - YCS25R_MODEL-PDF](#)
[3D Models - YCS25R_MODEL-IGES](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - 50115707](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YCS25R-SPEC-EN | REV 8/2023