

GP64526G1, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy
Catalog # GP64526G1

Raised Floor Grounding Clamp, #4 Sol. - 2/0 Str., 1.69 in L, 2.38 in.



Features

- Accepts 1 or 2 ground conductors, requiring less connectors to install signal reference grid
- Copper alloy, DURIMUM™ Silicon U-Bolts, Nuts and Lockwashers, proving a low impedance ground path for maximum performance
- Grounds all pedestals (Round or Square) from 3/4" to 1"
- UL467 Listed

Application

For Raised Floor Systems

General

Catalog Number	GP64526G1
EU RoHS Indicator	Yes
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Copper Alloy, Cast
Material - Hardware	DURIMUM™ Silicon Bronze
Pedestal Type	Round;Square
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Type	GP-G1
U Bolt Type	UB222
UPC	781810828014
UPC 12 Digit	7818108280144

Dimensions

Bolt Size	3/8 in
Dimension - B Length inch	1.50 in
Dimension - Height mm	0 mm
Dimension - L Length Overall mm	43 mm
Dimension - Length Overall inch	1.69 in
Dimension - Width inch	2.38 in

Dimension - Width mm 60 mm

Conductor Related

Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Size Range	2/0 AWG
Conductor Size	#4 AWG Sol - 2/0 AWG Str
Conductor Type	CU C Str-Size
Number of Conductors	1;2

Certifications And Compliance

Buy American Compliant	No
Certification - CSA Approved	No
Certification - UL Listed Direct	No
Burial	
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

[3D Models - GP654CG1_MODEL-PDF](#)
[3D Models - GP654CG1_MODEL-IGES](#)
[3D Models - GP654CG1_MODEL-STEP](#)
[Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_GP_LineArt](#)
[Sales Drawings - sd201549-01](#)
[Specifications - GP64526G1](#)