



208/277/380 - 95/115  
208/277/380 Primary Volts - 95/115 Secondary Volts - 1Ø  
Industrial Control Transformer - Open Core & Coil

1038



Catalog #: TB81301

#### PRODUCT FEATURES

- Meets or exceeds UL, CSA, NEMA, and ANSI standards
- UL Listed and CSA Certified
- Meets NEC Article 450
- Constructed out of electrical lamination with precision wound coils
- Primary and secondary fuse kits easily adaptable
- Add suffix "F2" to catalog for factory installed 2 pole primary block
- Add suffix "F4" to catalog for factory installed 2 pole primary and secondary fuse clips
- Covered under Acme's 10 year limited warranty

#### BENEFITS

- Series parallel connecting links save time and costs
- Mounting plate adapts to various mounting dimensions
- Molded terminal blocks allow easy ring terminal installation
- Optional Secondary Fuse Kits available

#### UL STANDARD

UL 506

#### CSA STANDARD

C22.2 No 66

#### WARRANTY

Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)

#### GENERAL PRODUCT INFORMATION

VA: 50  
Primary Voltage: 208/277/380  
Secondary Voltage: 95/115  
Frequency: 50/60 Hz  
Max Temperature Rise: 80°C  
UL Insulation Class: 130°C

#### PRODUCT MEASUREMENTS

Height (In./cm): 2.70 (6.8)  
Width (In./cm): 3.00 (7.6)  
Depth (In./cm): 4.35 (11.0)

#### CONFIGURATION

Mounting Type: Floor  
Primary Fuse Block: PL112700  
Wiring Diagram: E

**PACKAGING**

Ship Weight (Lbs/Kg): 4 (1.8)

**COMPLIANCES**

UL Standard: UL 506  
UL Listed: File E79947  
CSA Standard: C22.2 No 66  
CSA Listed: LR7357-16  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)