



# 9375-FR



VIDEO

## Product Description

4" dia. round fan support box for use with nonmetallic sheathed cable

**Catalog #:** 9375-FR

**Width:** 4 in.  
**Depth:** 3-13/16 in.  
**Volume:** 14 cu. in.

**Type of Installation:** Old or New Work  
**Round Ceiling Box**

**Carton Quantity:** 24  
**Carton Weight:** 7 lb.

**UPC:** 085339792918  
**UNSPSC:** 39121316

**Patents:**  
U.S. Patent No. 6,365,831 B1  
**Country of Origin:** United States of America

## FEATURES

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

## APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)  
*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches  
*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Black

## ADDITIONAL MATERIALS

Plated carbon steel fasteners

## MATERIAL

Polycarbonate

## SUPPORT RATING

110 lbs fixture support and 70 lbs fan support

## MOUNTING

Bottom mount