

## FIXTURES

<b>043X</b>	—		—	
PRIORI Xenon (Hardwire)		<b>1</b> = 10-1/4" length <b>2</b> = 14-1/2" length <b>3</b> = 22-1/2" length <b>4</b> = 32-1/2" length		<b>BS*</b> <b>DB*</b> <b>WH*</b>

<b>043X</b>	—		—	
PRIORI Xenon (Cord and Plug)		<b>1P</b> = 10-1/4" length <b>2P</b> = 14-1/2" length <b>3P</b> = 22-1/2" length		<b>BS*</b> <b>DB*</b> <b>WH*</b>

Note: Each hardwire fixture includes lamp(s) and 3/8" cable connector. Each cord and plug unit includes lamp(s) and six foot power cord. Captive screws (5/8" long) are standard.

\*Fixture finishes: BS = Brushed Steel, DB = Dark Bronze, WH = White

## ACCESSORIES



### 043J-BR, 043J-WH

Hardwire junction box for PRIORI fixtures, BR = Bronze, WH = White  
7-3/8"L x 2-1/8"W x 1"H; includes 12" extension and two 3/8" cable connectors, c/UL/us Listed



### 043X-20BP

120V Xenon replacement lamp  
20 watt bi-pin, G8; M.O.L. = 1-3/4"



### 043A-PC6-BK, 043A-PC6-WH

Six foot power cord for PRIORI fixtures, 120V AC grounded plug and 3-wire grounded molex connector, BK = Black, WH = White; c/UL/us Listed



### 043A-(LENGTH)-EX-(COLOR)

Black linking extensions (jumpers) for connecting multiple PRIORI fixtures; available in 6", 12", 24" and 36" lengths; BK = Black, WH = White; c/UL/us Listed

## TECHNICAL SPECIFICATIONS

Voltage	120V, 60Hz AC operation
Construction	Cold rolled steel housing, powder coat finish, full length aluminum reflector and plastic end caps with stand-offs for heat dissipation
Mounting	Mount to underside of shelf or cabinet, at leading edge for best performance; see also page 39.
Dimensions	H = 15/16", W = 3-3/4", available Lengths = 10-1/4", 14-1/2", 22-1/2" and 32-1/2"
Switching	High/Low/Off rocker switch
Knockouts	3/8" knockouts standard: every 4" along the back and every 4" along top of housing; or use hardwire junction box (043J, sold separately) which includes four 3/8" knockouts, two reducers/wire clamps and 'stab' connectors
Wattages	043X-1 = 20 watts, 043X-2 = 40 watts, 043X-3 = 60 watts, 043X-4 = 80 watts
Power cord	Six-foot power cord (043A-PC6, sold separately)
Maximum run	600 watts
Lamp specs	8,000 hour rated life, 100CRI, 2800K, G8 base, 20 watts, 120V, 1-3/4" M.O.L.
Dimmers	Dimmable with most standard incandescent dimmers
Diffuser	Full length, captive hinged lens cover with magnetic closure
Packaging	Retail box with hang tab, 6 boxes per case



P/H

