

LED FLEXBRITE KITS

Energy efficient UL Listed kits are easy to install

LED FLEXBRITE KITS

Save 82% in energy usage compared to incandescent. Great for accent lighting, decorative lighting, outlines, architectural details, patios, decks, gazebos and more.

FEATURES


- Indoor/outdoor rated
- LED Flexbrite kits include: Flexbrite, pre-connected removable five foot power cord, end cap and one mounting clip per foot of Flexbrite
- Kits are easily extendable up to 240 feet – attach multiple kits together (no tools required)
- Produces virtually no heat for maximum safety
- Highest quality PVC with UV inhibitor to maximize life
- Available in 6400K (Cool White) and 2700K (Ultra Warm White)



Ultra Warm White



Cool White



Interconnection of two kits

BILL OF MATERIALS

- ☐ Determine length needed to the nearest multiple of 3 feet, up to 240 feet
- ☐ Order kits in like sizes where possible
- ☐ Order mounting track for straight runs (recommended); clips are included with kits



KITS

LR-LED		
120V LED Flexbrite Kits	CW = Cool White UWW = Ultra Warm White	3 = 3' kits, 10 per case 9 = 9' kits 10 per case 15 = 15' kits, 10 per case 30 = 30' kits, 5 per case 75 = 75' kits, 1 per case 150 = 150' kits, 1 per case

Kelvin temperatures may not match across different length kits; use kits in like sizes as a rule.

ACCESSORIES



LR-LED-EXT3

Three foot jumper for Flexbrite kits only, white wire; includes two power connectors



RL-TRK-3

Three foot clear mounting track with UV rating for outdoors
Sold in case quantities of 40 only!



LR-CLIP-20

Blister pack of twenty clear mounting clips with screws



DL-CLIP/SCREW

Clear "U" shaped mounting clip



DL-TRACK-4

Four foot clear mounting track with UV rating for outdoors; recommended for use with straight line installations

TECHNICAL SPECIFICATIONS

Voltage	120V, 60Hz AC operation
Construction	Heat resistant clear PVC housing with LEDs every 1", vertical mount
Mounting	Clear plastic mounting clips or track
Dimensions	1/2" diameter
Cuttability	N/A
Light output	CW = 6.3 lumens per foot, UWW = 5.5 lumens per foot
Wattage	0.77 watt per foot
Maximum run	240 feet
Switching	Provide switched outlet for On/Off control
Linking	Interconnect kits with no additional parts or use LR-LED-EXT3 jumper for connecting two sections together
LED specs	60,000 hours, .067 watt, 1.11V, 60mA, 3mm, 120° beam angle; UWW (2700K) CRI = 73; CW (6400K) CRI = 80
Dimmers	Switched wall outlets cannot be used with wall dimmers per the NEC. Dimmable with most CFL/LED and low voltage electronic dimmers (minimum loads may apply).
Diffuser	Clear PVC jacket
Packaging	Retail blister packs (3', 9' and 15' lengths), retail boxes (30' lengths) or white cartons with color sticker (75' and 150' lengths)

