

ACCESSORIES



043J-BR, 043J-WH

Hardwire junction box for PRIORI fixtures, BR = Bronze, WH = White; 7-3/8"L x 2-1/8"W x 1"H; includes 12" extension and two 3/8" cable connectors, c/UL/us Listed



043A-(LENGTH)-EX-WH

White linking cables (jumpers) for connecting multiple PRIORI fixtures; available in 6", 12", 24" and 36" lengths; c/UL/us Listed



043A-PC6-BK, 043A-PC6-WH

Six foot power cord for PRIORI fixtures, 120V AC grounded plug and 3-wire grounded molex connector, BK = Black, WH = White, c/UL/us Listed



043A-(LENGTH)-EX-BK

Black linking cables (jumpers) for connecting multiple PRIORI fixtures; available in 6", 12", 24" and 36" lengths; c/UL/us Listed



043T-F06/30, 043T-F08/30, 043T-F13/30, 043T-F18/30, 043T-F24/30

120V T2 fluorescent replacement lamp, 3000K
Wattages, 6W, 8W, 13W, 18W, 24W;
10,000 hour rated life, CRI = 90



TECHNICAL SPECIFICATIONS

Voltage	120V, 60Hz AC operation
Construction	Cold rolled steel housing, powder coat finish, full length aluminum reflector and plastic end caps with stand-offs for heat dissipation
Mounting	Mount to underside of shelf or cabinet, at leading edge for best performance; see also page 39.
Dimensions	H = 15/16", W = 3-3/4", available Lengths = 10-1/4", 14-1/2", 22-1/2", 28-1/2" and 32-1/2"
Switching	On/Off rocker switch
Knockouts	3/8" knockouts standard: every 4" along the back and every 4" along top of housing; or use hardwire junction box (043J, sold separately) which includes four 3/8" knockouts, one 12" long "jumper cable", two reducers/wire clamps and pre-attached 'stab' connectors for quick connection
Light output	See table on facing page
Wattages	043T-10 = 6 watts, 043T-14 = 8 watts, 043T-22 = 13 watts, 043T-28 = 18 watts, 043T-32 = 24 watts
Maximum run	600 watts
Lamp specs	10,000 hour rated life, 90CRI, 3000K, axial base for T2 sockets, 120V
Dimmers	Not dimmable
Diffuser	Full length tempered glass lens with captive hinged lens cover and magnetic closure
Packaging	Retail box with hang tab, 6 boxes per case



P/H

