

Non-Metallic RAINBOX™

Made in USA 



Raintight Box for Exterior Fan/Fixture Installations



FBC4225W
White RAINBOX™

- Save time!...No field revisions
 - Raintight, UL Listed assembly
 - Completely sealed installation
- No exposed wiring**
No pests, dirt or moisture

Arlington's non-metallic RAINBOX™ is the raintight, labor-saving solution to installing a fan or fixture exposed to the elements, inside or outside. This box eliminates the need for time-consuming field modifications. It's completely sealed so water stays out and wiring stays dry. Plus, it supports a 70 lb fan or fixture securely and safely.

RAINBOX is perfect for any area with open exposure to wind-driven rain and water spray; anywhere you would install a wet- or damp-rated fan. Uses include pool screen enclosures, open porches, lanais, outdoor kitchens and eating areas, pavilions, greenhouses, barns and more.

- Oversized medallion accommodates canopies up to 7" in diameter
- Two colors: white and bronze
- UL/CSA Listed, raintight assembly
- NEC code-compliant. Completely sealed against water, dirt and pests – no exposed wiring

Easy, Raintight Installation in Wet or Damp Areas...



Install fitting with conduit. Seal unused openings with supplied plugs. Mount box to structural member.



Pull wire (not included).



Attach medallion to box with supplied #8 x 1-1/4" screws.



FBC4225W
White RAINBOX™
(exploded, with components)




Attach fan/fixture bracket to structural member using supplied long screws (#12 x 4"). Connect wires and install fan/fixture per manufacturer's instructions.



Catalog Number	UPC/DEI/NAED Mfg. #018997	Description RAINBOX™	Unit Pkg	Std Pkg
FBC4225W	09679	Color: White, Non-metallic 21.0 cu. inch box	1	5
FBC4225BR	09677	Color: Bronze, Non-metallic 21.0 cu. inch box	1	5

Includes 21.0 cu. inch RAINBOX™, medallion, (2) 1/2" to 3/4" NPT reducing bushings, (4) plugs, (2) #8 x 1-1/4" screws for medallion and (2) #12 x 4" screws for fan/fixture bracket.



Arlington

1 Stauffer Industrial Park
Scranton, PA 18517
800/233.4717
Fax 570/562.0646
www.aifittings.com