Wall Pak Pro 64 Watt **LED**



Glare Free



Design is Protected by US Patents D772,474; D752,274





LUMENS: 7,384

LUMENS PER WATT: 121

CCT: 4500K

WATTS: **64**

CRI: 82

DIMMING: 10-100%

MANUFACTURED-X
200000
20000
10000000
& TESTED IN USA



Ordering Information

CATALOG #	DESCRIPTION	VOLTS
WPM64LED	64W LED Wall Pak Pro	120-277

Options

ADD SUFFIX #	DESCRIPTION
PC	120V Photocontrol
PM	208-277V Photocontrol


Note: Atlas uses only premium LED compatible photocontrols


Performance

- Eliminates Glare & Offensive Light
- Less Wasted Light
- More Footcandles on the Ground
- Labor Saving: Quick and Secure Mounting


Dimensions and Specifications

Overall Height: 6.25" Overall Width: 9.29" Depth: 9.06" Weight: 10 lbs.





Recommended Mounting Height - 16-18 ft.



FOOTCANDLES ON THE GROUND								
Mtg.		90°			45°		Avg. FCs	
Hgt.	5'	10'	15'	5'	10'	15'	450 sq. ft.	
16'	13.0	8.7	5.3	12.2	8.2	4.9	8.7	
18'	10.5	7.6	5.0	10.0	7.3	4.7	7.5	









