

## Double-Sided Box Support Bracket w/ Marty-Mouse™ Ears



- c UL) us
- 1. Bracket is shipped with ear tabs in the open position



2. Insert box screws into open slots



- Double-side box support, designed for Pre-Fab. Unit can be installed on either side of stud without repositioning box or devices.
- Patented Marty Mouse™ ears feature an innovative keyhole pattern to secure outlet box to bracket with or without the plaster ring.
- Wider box opening accommodates one or two gang adjustable plaster rings (B1AJ & B2AJ).
- Enhanced far-side support stands up during drywall installation and out performs competitor brackets.
- Contact factory for pre-fab box assemblies.
- Finish: Pre-Galvanized.
- 3. When plaster ring is installed, the ear tabs are bent down into the closed position




4. With the tabs closed, the box remains secured to the bracket when the plaster ring is removed



UPC/Part Number	Catalog Number	Stud Size	Box Qty.
78205138645	BB73	35/8", 21/2"	50
78205138717	BB74	4", 3 <sup>5</sup> /8", 2 <sup>1</sup> /2"	50
78205138759	BB76	$6$ ", $5^{1}/2$ ", $3^{5}/8$ ", $2^{1}/2$ "	25

Patent # 5595362

Read safety/installation instruction sheets in packages before use. These products are designed for positioning only. No load rating.




## **Box Support Brackets**

- Interlocking wrap-around design provides extra rigidity.
- Supports most standard 1-gang and 2-gang US and Canadian boxes and/or plaster rings 4" SQ., 4<sup>11</sup>/<sub>16</sub>" SQ., and 5" SQ. on either side of the stud.



- Adjustable for varying stud depths (2½" to 6").
- Compatible with 1-gang and 2-gang Rapid Ring<sup>™</sup> and adjustable plaster rings.
- Integral mounting tabs for attaching plaster rings.
- Multiple brackets may be ganged together.
- Contact factory for pre-fab box assemblies.
- Finish: Pre-Galvanized.
- · Patent Pending.



UPC/Part Number	Catalog Number	Metal Stud Size	Box Qty.
79903856399	BB70	21/2" - 4"	50
79903856400	BB70E*	5 <sup>1</sup> /2" - 6"	50

<sup>\*</sup> Must be used with BB70.



Can be used with BBFS-18 (floor stand) See page 29.

Read safety/installation instruction sheets in packages before use. These products are designed for positioning only. No load rating.

## Bend For Various Depths







21/2"

35/8"



For 51/2" depth, snap the BB70E into the next notch on the bracket side

6"

## Bending Bracket for 35/8" depth













Read safety/installation instruction sheets in packages before use. These products are designed for positioning only. No load rating.