



BURNDY Catalog Number	KKA31U2N
UPC Number	781810370438
Description	6STR - 350 NEMA
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	1.25
Length (in)	5.5
Bolt Hole Size (in)	0.5
Thickness	0.38
D - in	3.16
Pad Width (in)	1.27
E - in	1.75
N (in)	0.63
General	
Number of Holes	2
Product Description	Aluminum Universal Terminal, 2 Hole, 6 AWG (Str)-350 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	6 AWG-350 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-350 kcmil
Physical	
Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	1/2
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Services
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175

