



BURNDY Catalog Number YGHC34C26
 UPC Number 781810221068
 Description 300-500 TO 1-2/0 GRD C T
 Status Active

Web Use
 BURNDY Product Line

Dimensional	
B Length (in)	0.88
Diameter (in) - Total	2.42
General	
Product Description	Copper Compression C Connector, 300-500 kcmil, 3/4" Rod (Run) & 6 AWG(Sol) - 2/0 AWG(Str) (Tap)
Conductor(s)	
Copper Tap Range	7 AWG-2/0 AWG
Copper Stranded Run (Range)	300 kcmil-500 kcmil
Rod Size Run (Range)	3/4 in
Copper Solid Tap (Range)	6 AWG-3/0 AWG
Rebar Run Size (Range)	N/A
Copper Solid Run Size (Range)	N/A
Physical	
Type of Plating	Unplated
Connector Type	Tap
Plated (Yes or No)	N
Index Number	1011
Product Material	Copper
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B,UL467,IEEE 837
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
 47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies
 47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175