



BURNDY Catalog Number YGHP34C2
 UPC Number 781810220955
 Description 250-500 TO 4-2 GRN CONN
 Status Active

Web Use
 BURNDY Product Line

Dimensional	
B Length (in)	2.31
B Length (Fraction)	2-1/3
General	
Product Description	Copper Compression Fig. 6 Connector, 250 kcmil - 500 kcmil/ 5/8" - 3/4" Ground Rod, 4 AWG (Sol) - 2 AWG (Str.) (TAP)
Prefilled (Oxide Inhibitor)	Y
Other	
Type of Oxide Inhibitor	Penetrox E
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467,IEEE 837
Conductor(s)	
Copper Tap Range	4 AWG-2 AWG
Copper Stranded Run (Range)	250 kcmil-500 kcmil
Copper Solid Tap (Range)	4 AWG-2 AWG
Copper Solid Run Size (Range)	N/A
Physical	
Type of Plating	Unplated
Connector Type	Tap
Plated (Yes or No)	N
Index Number	998
Product Material	Copper
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
 47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies
 47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175