



Galvanized Ground Rod, Pointed – 815860



- Meets ANSI®/NEMA® GR1
- Zinc-coated exteriors are hot-dip galvanized for solid protection against corrosion, in accordance with ASTM® specification A153-78
- Surfaces are rigidly inspected to eliminate seams, slivers and other defects



Part Number	815860
Material	Steel
Finish	Hot-Dip Galvanized
Tensile Strength	80,000 psi Min
Ground Rod Diameter, Nominal	5/8"
Ground Rod Diameter, Actual (Ø)	0.631"
Length (L)	6'
Unit Weight	6.4 lb
UPC Label	No
Standard Packaging Quantity	5 pc
UPC	78285630647

ANSI is a registered trademark of American National Standards Institute. ASTM is a registered trademark of American Society for Testing and Materials. NEMA is a registered service mark of National Electrical Manufacturers Association.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.