


Through Roof PVC Assembly, Parallel Conductor to Parallel Conductor – LPC66418



- Allows for lightning protection conductors to be concealed in ceiling or walls



Part Number	LPC66418
Conductor Size, UL	Class 1 - Class 2 (4/0 Max)
Material	Copper Polyvinylchloride Stainless Steel 18-8 (EN 1.4305)
Connection Material	Copper - Copper
Rod Length [L]	18"
Rod Size [RS]	1/2"
Outer Diameter [OD]	1.315"
Unit Weight	2.305 lb
Certifications	UL
Standard Packaging Quantity	1 pc
UPC	78285664533

Always consult the roof manufacturer or owner for proper flashing materials.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.