



# Cable to Cable to Ground Rod or Other Rounds – NCR182G



nVent ERICO Cadweld graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

- Forms a permanent, low resistance connection
- Provides a molecular bond
- nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor
- Portable installation equipment with no external source of power required
- Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections
- Connections can be visually inspected
- Meets requirements of the Buy American Act



Part Number	NCR182G
Ground Rod Type	Copper-bonded
Mold Family	NC
Ground Rod Diameter, Nominal	3/4"
Ground Rod Diameter, Actual	0.682"
Conductor 1	2/0 Concentric
Conductor 1 Outer Diameter, Nominal	0.418"
Conductor 2	2/0 Concentric
Conductor 2 Outer Diameter, Nominal	0.418"
Split Crucible	No
Wear Plates	No
Mold Only	No
Welding Material	200 or 200PLUSF20, Sold Separately
Handle Clamp	L160, Sold Separately
Price Key	R

Part Number	NCR182G
Ease of Use	Preferred
Standard Packaging Quantity	1 pc
UPC	78285654630

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.