




CADDY SLICK NUT – SLICK250



- Provides fast universal attachment of threaded rod and hardware to standard strut profiles



Part Number	SLICK250
Material	Polyamide Spring Steel
Finish	CADDY ARMOUR
Hole Size (HS)	1/4"
Hole Type	Threaded
Height (H)	11/16"
Torque (TQ)	4 ft lb
Static Load 1 (F1)	400 lb
Static Load 2 (F2)	100 lb
Static Load 3 (F3)	250 lb
Standard Packaging Quantity	100 pc
UPC	78285641671

Indicated loads are independent of the threaded stud or rod.

Indicated loads are applicable on 14 GA and 12 GA (2 mm and 2.5 mm) strut channels only.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

