

Strut Nut with Top Spring – TSNT0025EG



- Used to create metal frames with CADDY ERISTRUT channels •
- Spring allows for easy installation





Part Number	TSNT0025EG
Material	Steel
Finish	Electrogalvanized
Static Load Safety Factor	3:1
Rod Size (RS)	1/4"
Thickness (T)	1/4"
Torque (TQ)	6 ft lb
Standard Packaging Quantity	100 рс
UPC	78285634076

Pull-Out Strength				
Part Number	Channel Type	Channel Thickness		
		12 GA	14 GA	
TSNT0025EG	A, C	450 lb	450 lb	
	D, E	450 lb	-	
TSNT0037EG	A, C	1,100 lb	1,000 lb	
	D, E	1,100 lb	-	
TSNT0050EG	А	2,000 lb	1,400 lb	
	D, E	1,500 lb	-	

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



