




**PACESETTER
COMPACT FLUORESCENT TRIMS**




R12P White Albalite
O.D.: 8" (203 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 12
Ship Wt.: 8




R16P White Drop Opal
O.D.: 8" (203 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 7



RMA99 White Reflector, **QS**
Self-lipped Trim.
Accepts no trim accessories.
O.D.: 7" (178 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 4




R25P White Wall Wash
O.D.: 8" (203 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 6




RMA100CLR
Clear Alzak® Reflector **QS**
RMA100GLD
Gold Alzak® Reflector **QS**
RMA100BLK
Black Alzak® Reflector
O.D.: 7 1/16" (179 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 5


**RECESSED
FLUORESCENT**



RMA101 Clear Reflector
with Black Baffle **QS**
RMA101W Clear Reflector
with White Baffle
O.D.: 7 1/16" (179 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 5



PSH12P Polycarbonate Shower Light,
Opal Lens **QS**
U.L. Wet Location Listed.
O.D.: 8" (203 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 12
Ship Wt.: 3 1/2




PSH17P Polycarbonate Shower Light,
Drop Opal Lens **QS**
U.L. Wet Location Listed.
O.D.: 8" (203 mm)
Lamp: **(1) CFQ13W/GX23**
Std. Pack: 6
Ship Wt.: 7

**CAPRI®
LIGHTING**

6
INCH
DIAMETER

Note: **QS** Quick Ship products are normally stocked at the factory and available for immediate shipment.

6
INCH
DIAMETER




QL07/120

Descript.: For new construction. Thermally protected, labor saving, recessed housing. Engineered polymer plaster frame includes pre-positioned nails for fast installation. Adjustable socket mounting plate. Four Romex knockouts and two 1/2" conduit knockouts. Uses 13 watt CFQ13W/GX23 fluorescent lamp, not included. Standard in 120V Normal Power Factor. U.L. listed for Damp Locations and Through-Branch Circuit Wiring. Height: 7 1/2" (191 mm), Length: 14 1/4" (362 mm), Width: 8 1/2" (216 mm), Ceiling Opening: 6 1/4" (159 mm)

Std. Pack: 6

Ship Wt.: 19



PL07/120 CS


PL07/120HPF

PL07/277HPF

Descript.: For new construction. Thermally protected, recessed housing. Includes BH6 SURE-LOK® bar hangers and adjustable socket mounting plate. Remodel capability. Five 1/2" conduit knockouts and 4 Romex knockouts. Uses 13 watt CFQ13W/GX23 fluorescent lamp, not included. Standard in 120V Normal Power Factor. U.L. listed for Damp Locations and Through-Branch Circuit Wiring. Height: 7 1/2" (190 mm), Length: 12 1/2" (318 mm), Width: 7 3/4" (197 mm), Ceiling Opening: 6 1/4" (159 mm)

Std. Pack: 6

Ship Wt.: 32



PL07IC/120 CS


Descript.: Insulated ceiling housing. Uses 13 watt CFQ13W/GX23 fluorescent lamp, not included. For use in direct contact with thermal insulation. Pre-installed BH6 bar hangers for use in joists 16" to 24" (406 mm to 610 mm) on center. Standard in 120V Normal Power Factor. U.L. listed for Damp Locations and Through-Branch Circuit Wiring. Height: 7 3/4" (197 mm), Length: 12 1/2" (318 mm), Width: 7 3/4" (197 mm), Ceiling Opening: 6 1/4"

Std. Pack: 4

Ship Wt.: 28

PL07ASIC/120

Descript.: Air Seal™ IC rated housing. Same features as PL07IC/120 above. Sealed to prevent passage of air to/from the ceiling plenum. Meets all WSEC requirements.



PLR07/120

PLR07/120HPF

Descript.: Remodel housing. Uses 13 watt CFQ13W/GX23 fluorescent lamp, not included. For installation in existing finished ceilings. Pre-installed clips secure the housing firmly into the ceiling. Use in ceiling thicknesses from 1/4" to 1 1/4" (6 mm to 32 mm). Standard in 120V Normal Power Factor. U.L. listed for Damp Locations and Through-Branch Circuit Wiring. Height: 7 3/4" (197 mm), Length: 14" (355 mm), Width: 6 1/4" (159 mm), Ceiling Opening: 6 1/4" (159 mm)

Std. Pack: 6

Ship Wt.: 15

OPTIONS

BH3 Pair 27" (686 mm) Flat Bar Hangers.

RF Radio Interference Filter.

Note: **CS** Quick Ship products are normally stocked at the factory and available for immediate shipment.