


# IN-LINE HEATER

## INSIDE-THE-PIPE POTABLE WATER HEATING CABLE

With a user-friendly plug-in installation, the In-Line Heater is an inside-the-pipe heating cable that provides an economical method to help maintain running water in 3.18 centimeters (1.25 inches) PE pipes all winter long. Adaptors are available for 2.54 centimeters (1 inch) pipes. It can be used in insulated pipes and will not melt through the pipe if dryout occurs. The In-Line Heater is CSA Certified for potable water.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
ILH4010	3.05m (10ft) length, 50 Watts	1	2.13kg (4.7lb)	0-69996-00302-0	
ILH4020	6.10m (20ft) length, 100 Watts	1	2.27kg (5lb)	0-69996-00303-7	
ILH4030	9.14m (30ft) length, 150 Watts	1	2.36kg (5.2lb)	0-69996-00304-4	
ILH4040	12.20m (40ft) length, 200 Watts	1	2.72kg (6lb)	0-69996-00318-1	
ILH4050	15.24m (50ft) length, 250 Watts	1	2.59kg (5.7lb)	0-69996-00305-1	
ILH4060	18.29m (60ft) length, 300 Watts	1	3.18kg (7lb)	0-69996-00319-8	
ILH4070	21.34m (70ft) length, 350 Watts	1	2.77kg (6.1lb)	0-69996-00306-8	
ILH4090	27.43m (90ft) length, 450 Watts	1	2.99kg (6.6lb)	0-69996-00307-5	
ILH4100	30.48m (100ft) length, 500 Watts	1	3.08kg (6.8lb)	0-69996-00308-2	
ILH4120	36.58m (120ft) length, 600 Watts	1	3.27kg (7.2lb)	0-69996-00309-9	
ILH4140	42.67m (140ft) length, 700 Watts	1	3.49kg (7.7lb)	0-69996-00310-5	
ILH4160	48.77m (160ft) length, 800 Watts	1	3.72kg (8.2lb)	0-69996-00311-2	
ILH4180	54.86m (180ft) length, 900 Watts	1	3.90kg (8.6lb)	0-69996-00312-9	
ILH4200	60.96m (200ft) length, 1000 Watts	1	4.13kg (9.1lb)	0-69996-00313-6	
ILH4225	68.58m (225ft) length, 1125 Watts	1	4.35kg (9.6lb)	0-69996-00314-3	
ILH4250	76.20m (250ft) length, 1250 Watts	1	4.63kg (10.2lb)	0-69996-00315-0	
ILH4270	82.30m (270ft) length, 1350 Watts	1	4.81kg (10.6lb)	0-69996-00316-7	
10561001	3.18 to 2.54cm (1.25in to 1in) adaptor (2 required per Philmac fitting)	1	0.45kg (1lb)	0-69996-00325-9	

# CONTROLS

## RESIDENTIAL PIPE TRACING CONTROLS

Intended for temperature control of a variety of electric heating cables and applications.

**SL2G** – The energy-saving SL2G thermostat with built-in GFCI is intended for temperature control of In-Line Heater cable sets and is CSA Certified.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SL2G	GFCI thermostat control; 12 Amp, 120 Vac, 1° to 35°C (34° to 95°F)	1	1.0kg (2.2lb)	0-13627-09931-9	