

Type CL

Part of the **CORRLOK® / Reiku Nylon System.**

CL is a nonmetallic UL Recognized nylon corrugated Mechanical Protection Tubing (MPT) designed for the support and routing of conductors and cables. It is used as a UL / CSA component within OEM equipment.

Construction:

- Made from a specially compounded homogenous nylon 6 material
- Corrugated for flexibility and strength

Application:

- Intended to be used to interconnect separate component assemblies or consoles of electrical devices
- Medical and X-ray equipment
- Electronics
- Fiber Optics
- Wire Harnesses

Fittings:

Type CL is intended to be used only with the CF series of the CORRLOK® / Reiku System connectors and adapters.




Sizes 5/16" through 1" are Proudly Made in the USA



Product Information

CERTIFICATIONS & COMPLIANCE

 Conforms to UL 1696 CSA 22.2 No. 227.3 Harmonized Standard



WEEE and RoHS Compliant

STANDARD WEIGHT

Black

WORKING TEMPERATURES:

-40°C to 105°C Intermittent to 150°C

Product Table

U.S. Trade Size	MM	NW	Type	Reiku		Nominal Dimensions		Inside Static Bend Radius	Weight	Standard Length	
				Grey	Black	Inside (in)	Outside (in)			In.	lb/100 ft
1/4"	10	7	CL-140	PA RE G-07G	PA RE B-07G	0.252	0.394	0.6	1.5	100	79001
5/16"	12	10	CL-516	PA RE G-10F	PA RE B-10F	0.378	0.512	0.8	1.7	100	79071
3/8"	16	12	CL-10	PA RE G-12F	PA RE B-12F	0.469	0.610	1.2	2.2	100	79081
1/2"	20	17	CL-11	PA RE G-17F	PA RE B-17F	0.654	0.835	1.4	3.7	100	79181
3/4"	25	23	CL-12	PA RE G-23F	PA RE B-23F	0.898	1.114	1.8	5.9	100	79281
1"	32	29	CL-13	PA RE G-29F	PA RE B-29F	1.106	1.358	2.6	8.1	50	79381
1-1/4"	40	36	CL-14	PA RE G-36F	PA RE B-36F	1.425	1.673	3.3	9.2	50	79481
1-1/2"	50	48	CL-15	PA RE G-48F	PA RE B-48F	1.878	2.146	3.7	12.3	50	79581
2-1/2"	70	70	CL-17	PA RE G-70G	PA RE B-70G	2.756	3.248	6.3	29.7	30	79686
3-1/2"	95	95	CL-350	PA RE G-95G	PA RE B-95G	3.543	4.173	8.3	48.2	30	79886

related products



Type CLR

CLR is a nonmetallic nylon corrugated Mechanical Protection Tubing (MPT) designed for the support and routing of conductors and cables.

[see product detail »](#)



Type CLFR

CLFR is a Low Fire Hazard nonmetallic nylon corrugated Mechanical Protection Tubing (MPT) designed for the support and routing of conductors and cables.

[see product detail »](#)



Type NMHT

This version of Type NM is designed to withstand high temperature environments. NMHT can be used to contain conductors having insulation materials with higher temperature ratings.

[see product detail »](#)



Type NM2

Type NM2 is an extra-flexible liquidtight nonmetallic tubing. This lightweight tubing cuts easily and installs quickly. It is ideal for wiring protection in tight quarters and for tight bends. The thin, flexible PVC skin allows for greater movement than Listed nonmetallic conduits.